



PF-E1.5 LDPE Film

Product Application & Description

PF-E1.5 is a clear 1.5 mil. low density polyethylene (LDPE), offering excellent "hot tack" when used in sealing applications. Provides low temperature seal ability with good puncher resistance and impact strength when used in multi-layer laminated constructions.

Shelf Life & Storage

It is recommended to consume all materials within 1 year from date of purchase. Best if stored in a controlled environment (72°F and 50% RH) and out of direct sunlight.

Technical Data	
Properties	Value
Melt Ind (G/10 Min.)	1.0
Film Haze	5.5 to 6.0%
Gloss, 45	75
Dart Impact (Method B).g	> 830
Tensile Modulus (2% Secant MD/TD)	14,120 MD/14060 TD
Ultimate Elongation (MD/TD)	585 MD/630 TD
Elmendorf Tear (MD/CD)	560 MD/630 CD
COF	9.5
<i>Tested in a normal laboratory condition: 23°C at 50% relative humidity.</i>	

Please Note: The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.